

## Easy Living Gloss Enamel (ELE range)

### Section 1. Identification

**GHS product identifier** : Easy Living Gloss Enamel (ELE range)

**Other means of identification** : A high quality solvent based enamel with a high gloss finish.

**Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** : Used as a decorative and protective finish on interior and exterior mild steel, galvanised steel, timber and masonry.

**Supplier's details** : Kansai Plascon (Pty) Ltd  
P.O. Box 4010  
Luipaardsvlei  
1743

**Emergency phone** : (011) 951 4500 (within hours of operation)

**Facsimile** : (011) 955 2841

**National Contact Person** : Mr C. Costa

### Section 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE LIQUID- Category 3  
SKIN CORROSION/ IRRITATION-Category 2  
ACUTE TOXICITY - Category 4  
SERIOUS EYE DAMAGE/ IRRITATION- Category 2  
SPECIFIC TARGET ORGAN TOXICITY SINGLE EXPOSURE- Category 3  
ASPIRATION TOXICITY- Category 1  
AQUATIC TOXICITY CHRONIC- Category 2

**Label elements according to** : SANS 10234: 2008

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : H226- Flammable liquid and vapour.  
H303- May be harmful if swallowed.  
H304- May be fatal if swallowed and enters airways  
H312- Harmful if in contact with skin  
H315- Causes skin irritation.  
H319 – Causes serious eye irritation  
H332- Harmful if inhaled  
H336- May cause drowsiness or dizziness  
H411- Toxic to aquatic life with long-lasting effects



## Easy Living Gloss Enamel (ELE range)

---

### Precautionary statements

- General : P101- If medical advice is needed, have product container or label at hand.  
P102- Keep out of reach of children.  
P103- Read label before use.
- Prevention : P202- Do not handle until all safety precautions have been read and understood.  
P501: Dispose of contents/containers in accordance with local regulation.  
P233- Keep container tightly closed.  
P261- Avoid breathing vapours/spray.  
P262- Do not get in eyes, on skin, or on clothing.  
P270- Do not eat, drink or smoke when using this product.  
P271- Use only outdoors or in a well-ventilated area.  
P273- Avoid release to the environment.  
P280- Wear protective gloves/protective clothing/eye protection/face protection.  
P285- In case of inadequate ventilation wear respiratory protection.  
P235+410- Keep cool. Protect from sunlight
- Response : P314- Get medical advice/attention if you feel unwell.  
P391- Collect spillage.  
P301+330+331- IF SWALLOWED- Rinse mouth. Do NOT induce vomiting.  
P303+361+353- IF ON SKIN (or hair)- Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304+340: IF INHALED- Remove person to fresh air and keep comfortable for breathing.  
P305+351+338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.  
P333+313- If skin irritation or a rash occurs: Get medical advice/attention.  
P337+313- If eye irritation persists get medical advice/attention.  
P361+364- Take off immediately all contaminated clothing and wash it before reuse.  
P362+364- Take off contaminated clothing and wash it before reuse.



## Easy Living Gloss Enamel (ELE range)

P370+380- In case of fire: Evacuate area.

Storage : P410- Protect from sunlight.

P402+404- Store in a dry place. Store in a closed container.

P403+235- Store in a well ventilated place. Keep cool.

Other hazards which do not  
Result in classification : None identified

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : Solvent based enamel

CAS number/other identifiers

CAS number : Not applicable

Ingredient name	CAS number	%	SANS 10234 Classification
Medium Aliphatic Petroleum Solvent	64742-88-7	20.0-30.0	Acute Tox. 4, H332 Acute Tox. 5, H303 Asp. Tox 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Aquatic Chronic 2, H411 Flam. Liq. 3, H226
Hydrocarbon blend (C9-C11 n-Paraffins)	64771-72-8	5.0-15.0	Flam. Liq. 3, H226 Asp. Tox 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412
Heavy Aromatic Petroleum Solvent	64742-94-5	<10.0	Acute Tox. 4, H332 Acute Tox. 5, H303 Asp. Tox 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Aquatic Chronic 2, H411 Flam. Liq. 3, H226
Xylene	1330-20-7	<2.0	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.



## Easy Living Gloss Enamel (ELE range)

### Section 4. First aid measures

Description of necessary first aid measures

- Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/ effects, acute and delayed

##### Potential acute health effects

- Eye contact : Causes serious eye irritation.
- Inhalation : Harmful if inhaled. Irritating and narcotic. Can affect central nervous system.
- Skin contact : Harmful if in contact with skin. Risk of dermatitis.
- Ingestion : Harmful if swallowed.

##### Over-exposure signs/symptoms

- Eye contact : Adverse symptoms may include pain or irritation, watering or redness.
- Inhalation : Adverse symptoms may include nausea or vomiting, headache, drowsiness/fatigue or dizziness/vertigo.
- Skin contact : Adverse symptoms may include irritation or redness.
- Ingestion : May cause damage to organs through prolonged or repeated exposure.

#### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments : No specific treatment.
- Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

#### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### Extinguishing media

- Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire such as foam, CO<sub>2</sub> or dry powder. Use fog to cool and control.



## Easy Living Gloss Enamel (ELE range)

Unsuitable extinguishing media : Do NOT use water jets.

**Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. Cool containers in case of fire.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials  
carbon dioxide  
carbon monoxide  
metal oxide/ oxides

**Special protective actions For fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.


For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal



## Easy Living Gloss Enamel (ELE range)

according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

### Section 7. Handling and storage

#### Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep away from ignition sources. No open flames. No smoking. Avoid free fall of liquid – use earthing.

#### Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Section 8. Exposure controls/personal protection

#### Occupational exposure limits

Ingredient name	Exposure limits
Hydrocarbon blend (C9-C11 n-Paraffins)	<b>ACGIH:</b> TWA: 350 mg/m <sup>3</sup>
Heavy Aromatic Petroleum Solvent	<b>ACGIH TLV:</b> TWA: 525 mg/m <sup>3</sup> TWA: 100ppm
Xylene	<b>OHSA:</b> TWA STEL: 150 ppm TWA STEL: 655 mg/m <sup>3</sup>

#### Recommended monitoring Procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

#### Appropriate engineering controls

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.



## Easy Living Gloss Enamel (ELE range)

### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Avoid direct contact. Never touch eyes with dirty hands or gloves. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

#### Hand protection

: Avoid direct contact. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

#### Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Avoid direct contact. Appropriate footwear and any additional skin protection Measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator with organic vapour filter cartridge (e.g. A1B1E1 type) complying with an approved standard if a risk assessment indicates this is necessary e.g. in case of insufficient ventilation. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

#### Physical state

: Viscous liquid

#### Colour

: White (ELE 1) and standard colours as per colour card. Also available in a wide range of INSPIRED COLOUR tints: Pastel (ELE 1000), Deep (ELE 2000), Transparent (ELE 3000)

#### Odor

: No data available

#### Odor threshold

: No data available

#### pH

: Not applicable



## Easy Living Gloss Enamel (ELE range)

Melting point	: Not applicable
Boiling point	: No data available
Flash point	: >23°C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Lower and upper explosive (flammable) limits	: No data available
Vapor pressure	: No data available
Vapor density	: No data available
Relative density	: 1.08 (Typical)
Solubility	: Soluble in organic solvents, insoluble in water
Partition coefficient, n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: 68 – 72 KU

### Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	: Inert - no reaction with fire-fighting water.
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.





## Easy Living Gloss Enamel (ELE range)

### Section 11. Toxicological information

#### Acute Toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Xylene	LC50 Inhalation Gas LD50 Oral	Rat Rat	5000 ppm 4300 mg/kg	4 hours -

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Xylene	Eyes - Mild irritant Skin - Moderate irritant	Rabbit Rabbit	- -	87 milligrams 100 Percent	- -

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target Organs
Hydrocarbon blend (C9-C11 n-Paraffins)	Category 3	Not determined	Not determine

#### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target Organs
None			

#### Aspiration hazard

Name	Result
Medium Aliphatic Petroleum Solvent	ASPIRATION HAZARD - Category 1
Heavy Aromatic Petroleum Solvent	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Inhalation, skin and eye contact

#### Potential acute health effects

Eye contact : Causes serious eye irritation.  
 Inhalation : Harmful if inhaled. Irritating and narcotic. Can affect central nervous system.  
 Skin contact : Harmful if in contact with skin. Risk of dermatitis.  
 Ingestion : Harmful if swallowed.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Pain or irritation, watering and redness.  
 Inhalation : Nausea, headache, drowsiness/fatigue, dizziness/vertigo.  
 Skin contact : Irritation, redness  
 Ingestion : May cause damage to organs through prolonged or repeated exposure.

#### Potential Chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.  
 Carcinogenicity : No known significant effects or critical hazards.  
 Mutagenicity : No known significant effects or critical hazards.  
 Teratogenicity : No known significant effects or critical hazards.  
 Developmental effects : No known significant effects or critical hazards.  
 Fertility effects : No known significant effects or critical hazards.



## Easy Living Gloss Enamel (ELE range)

Acute toxicity estimates  
No data available

### Section 12. Ecological information

#### Toxicity

Product/Ingredient name	Result	Species	Exposure
Hydrocarbon blend (C9-C11 n-Paraffins)	Acute EC50: 2990 ppm	Aquatic Toxicity: Bluegill sunfish	24 hours
Xylene	Acute LC50 8500 ug/L Marine water	Crustaceans - Palaemonetes Pugio	48 hours
	Acute LC50 3300 to 4093 ug/L Fresh water	Fish - Oncorhynchus mykiss - 0.6 g	96 hours

#### Persistence and degradability

Product/Ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbon blend (C9-C11 n-Paraffins)	-	-	Not readily biodegradable
Xylene	Fresh water <28 days	-	-

#### Bioaccumulative potential

Product/Ingredient name	LogP <sub>ow</sub>	BCF	Potential
Hydrocarbon blend (C9-C11 n-Paraffins)	3.3 and 5.25	190 to 5800	-
Xylene	3.12	20	Low

#### Mobility in soil

Soil/ water partition coefficient (K<sub>oc</sub>) : No data available.  
Mobility : No data available.

**PBT/vPvB data** : P: No data available. B: No data available. T: No data available.

**Other adverse effects** : No known significant effects or critical hazards.

### Section 13. Disposal considerations




**Disposal methods** : This material and its container must be disposed of in a safe way. The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor – potential for spontaneous combustion. Take care with used containers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill



## Easy Living Gloss Enamel (ELE range)

should only be considered when recycling is not feasible. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	Transportation - road - SANS 10228:2012	Transportation- Maritime - IMO/ IMDG	Transportation- Air - IATA
UN number	1263	1263	1263
UN proper shipping name	Paint related material	Paint related material	Paint related material
Transport hazard class(es)	3 	3 	3 
Packing group	III	III	III
Marine pollutant	No	No	No
Additional information	No data available	Emergency schedules (EmS) F-A, S-F	<b>Passenger and Cargo Aircraft</b> Quantity limitation: 450 L Packaging instructions: 964 <b>Cargo Aircraft Only</b> Quantity limitation: 450 L Packaging instructions: 964 <b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 30 kg Packaging instructions: Y964
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No data available	No data available	No data available

## Easy Living Gloss Enamel (ELE range)

### Section 15. Regulatory information

#### Safety, health and environmental regulations specific for the product

**: Relevant information regarding authorization:** Occupational Health and Safety Act 1993 Regulation for Hazardous Chemical Substances.  
**Relevant information regarding restrictions:** None known.  
**EU regulations:** Regulation EC 1272/2008 [EU-GHS/CLP] and EU directives 67/548/EEC or EC 1999/45/EC  
**Other National regulations:** None. Standards used for PPE recommendations in Section 8: NIOSH-National Institute for Occupational Health and Safety (USA) EN 166- European standard which concerns the area of eye protection. EN 374-3 European standards for permeation and penetration. EN 141/EN 143 European standards for gas mixtures to remove specified gases and vapours or combined filters for removing solids, and/or liquid particles and specified gases and vapours.

### Section 16. Other information

#### History

Date of printing : 13/07/2017

Date of previous issue : 20/06/2017

#### Key to abbreviations

: ATE = Acute Toxicity Estimate  
 BCP Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogP<sub>ow</sub> = logarithm of the octanol/water partition coefficient  
 MARPOL 73/78 = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
 UN = United Nations

#### References

: Supplier safety data sheets

#### Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

#### Notice to readers:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees.

This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

#### Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be only used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

