

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Designer Walls Metallic Paint (DRM Range)

**Company Name:** Kansai Plascon (Pty) Ltd  
**Address:** P.O. Box 4010  
 Luipaardsvlei  
 1743

**Telephone:** (011) 951-4500  
**Facsimile:** (011) 955-2841  
**Contact Person:** Mr C.Costa

## SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

**Chemical Class:** Water-based Acrylic Paint  
**Classification:** Non-hazardous  
**R Phrases:** None  
**S Phrases:** S2, 24/25

Hazardous and/or other relevant Components	% (w/w)	CAS No.	E.C. No.
ETHYLENE GLYCOL	< 25 %	107-27-1	603-027-00-1
PROPYLENE GLYCOL	< 10 %	57-55-6	-

## SECTION 3. HAZARDS IDENTIFICATION

**SAPMA Health Rating:** 4-MINIMAL – No great risk to health  
**Inhalation:** Irritating.  
**Skin:** No hazard expected if used in moderation.  
**Eyes:** May cause irritation. Avoid contact.  
**Ingestion:** Irritating and nauseating.

No carcinogenic, mutagenic or genetic effects established.  
 Non toxic but may have undesirable environmental side effects.



## SECTION 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. In case of discomfort seek medical attention.  
**Skin:** Always wash after being in contact with chemical substances.  
**Eyes:** Rinse immediately with plenty of water. Seek medical advice if discomfort persists.  
**Ingestion:** Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical attention.

## SECTION 5. FIRE FIGHTING MEASURES

Drier residues may be combustible with toxic fumes.  
 No direct explosion hazard expected.  
 In case of fire use foam, CO<sub>2</sub>, dry powder. Use fog to cool and control. Do NOT use water jets.

## SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Ensure sufficient ventilation.  
 Contain & collect spillage with non-combustible absorbent material and dispose of according to local regulations.  
 Do not allow product to enter drains and sewers.

## SECTION 7. HANDLING AND STORAGE

Store away from direct sun, heat and severe cold.  
 Preferably store in well ventilated area.  
 Avoid open flames. No smoking.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

NAME	CAS	OEL (mg/m <sup>3</sup> )	OEL (ppm)	STOEL (mg/m <sup>3</sup> )	STOEL (ppm)
ETHYLENE GLYCOL	107-27-1	60	-	125 RL	-
PROPYLENE GLYCOL	57-55-6	470	220	-	-

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

**SAPMA Rating:** 4-H-E PPE - Respirator and Eye protection  
**Inhalation:** In case of insufficient ventilation, use suitable respiratory protection.  
**Skin:** Avoid contact. Use only as directed.  
**Eyes:** Avoid direct contact. Never touch eyes with dirty hands or gloves.  
**Ingestion:** Observe the rules of hygiene. Wash before eating, drinking or smoking.



## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Viscous liquid  
**pH:** 8.0 – 9.0  
**Density:** 1.05 (typical)  
**Viscosity:** 100 - 110  
**Solubility:** Water miscible

## SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions. Inert - no reaction with fire-fighting water

## SECTION 11. TOXICOLOGICAL INFORMATION

No carcinogenic, mutagenic or genetic effects established

## SECTION 12. ECOLOGICAL INFORMATION

Non-toxic but may have undesirable side effects.

## SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

## SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous for transport.

## SECTION 15. REGULATORY INFORMATION

**Classification:** Non-hazardous  
S2 Keep out of the reach of children  
S24/25 Avoid contact with skin and eyes

## SECTION 16. OTHER INFORMATION

In case of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.