

POLYCELL BRUSH CLEANER

PRODUCT CODE: 502205

TECHNICAL DATA SHEET

Product Description	A powerful solvent based cleaner which is water rinse-able.	
Intended Uses	<ul style="list-style-type: none"> For cleaning of paintbrushes and rollers. General cleaning and degreasing of garage floors and driveway paving. Ideal for cleaning oils and grime build-up in kitchens, baths, ceramic tile areas, etc. POLYCELL BRUSH CLEANER is also recommended for the removal of tar and waxes from floors, car bodies, etc. An effective cleaner for removing dirt and paint spots on most clothing fabric and carpets Suitable for degreasing other cold surfaces such as car engines, factory machinery and agricultural equipment. 	
Features & Benefits	<ul style="list-style-type: none"> A powerful solvent based cleaner that can be easily rinsed with water. 	
Product Information	Colour	Clear
	Generic type	Solvent detergent cleaner
	S G	0.840
	Flash point	12 °C - Highly flammable
Application Details	Mixing	Ready for use.
	Method	Cloth, brush, hard bristle brush, sponge.
	Thinning	For heavy duty cleaning use as supplied. For removal of light greases and oils (e.g. enamel painted walls) dilute up to 50% with water.
	Cleaning	Water
Storage and Packaging	Store away from direct sun, heat and severe cold. Packaging: 500 ml	
Application	<ul style="list-style-type: none"> For cleaning brushes and rollers: Pour a small amount of POLYCELL BRUSH CLEANER into a suitable clean container. Work it thoroughly into the brush or roller. Then rinse brush or roller well with water until water is no longer milky. Hang brush or roller up to dry. Allow the mixture remaining in the container to separate. The clear top layer may be re-used. If the enamel paint has dried completely on the brush, it should first be soaked in REMOVAL ALL PURPOSE PAINT REMOVER (RRA 220) allowing the paint to soften and blister and then further cleaned with POLYCELL BRUSH CLEANER. For heavy duty degreasing (e.g. uncoated garage floors and drive-ways): Swab POLYCELL BRUSH CLEANER onto the soiled areas using a bristle brush or broom and work the solution well into the surface. Leave for approximately 15 minutes then flush off thoroughly with water while scrubbing with the brush or broom. Heavy deposits and deeply penetrated oil stains may require repeated applications. In such cases allow surface to dry before re-applying POLYCELL BRUSH CLEANER. Areas to be painted: Ensure that a water break-free surface is attained and rinse thoroughly until the water wash is clean and no longer milky. For clothing fabric and carpets: Swab POLYCELL BRUSH CLEANER liberally onto the soiled area using a cloth or sponge, dabbing and rubbing gently. Apply until the soil mark has disappeared. Apply clean water in a similar way until all the POLYCELL BRUSH CLEANER has been washed out of the fabric. Rub dry gently. 	
Cautions	<ul style="list-style-type: none"> Do not use on plastic, painted areas and other surfaces that may be attacked by the solvents. If unsure apply POLYCELL BRUSH CLEANER in an inconspicuous spot to check if substrate is attacked. After use always ensure that all traces of POLYCELL BRUSH CLEANER are rinsed off. When cleaning fabric first do a test on a small inconspicuous area to ensure that POLYCELL BRUSH CLEANER will not damage the fabric. Do not keep the product in contact with the fabric for longer than absolutely necessary. If using POLYCELL BRUSH CLEANER to degrease an engine, note that it may remove grease from bearings and soften plastic parts. 	



POLYCELL BRUSH CLEANER

PRODUCT CODE: 502205

Safety Precautions

- Always keep out of reach of children.
 - Ensure good ventilation during application and drying.
 - If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.
 - Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.
 - Harmful if swallowed. Seek medical attention and do not induce vomiting.
 - Do not smoke during use.
 - Flammable. Keep away from heat, flame and sparks.
 - Refer to Safety Data Sheet for complete information.
-

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za

