

WOODCARE KNOT SEAL

PRODUCT CODE: PK 2

TECHNICAL DATA SHEET

Product Description	A quick drying clear sealer.													
Intended Uses	<ul style="list-style-type: none"> Suitable for all interior and exterior wood surfaces For knots and other resinous areas in wood that prevents discolouration and blistering. 													
Features & Benefits	<ul style="list-style-type: none"> KNOT SEAL protects coatings from reacting with the resins present in knots by forming an impervious barrier between the resinous areas and the paint coatings. 													
Product Information	Appearance	Gloss												
	Colour	Clear												
	Solids	17% by volume												
	Viscosity at 23 °C	13 Sec FC4 (typical)												
	VOC	661 g/L												
Application Details	Mixing	Stir												
	Method	Brush only.												
	Thinning	No thinning required. Ready for use.												
	Cleaning	METHYLATED SPIRITS												
	Drying time	Touch dry: 5 mins @ 23 °C Over coating: 1 h @ 23 °C												
	Application environment	<table border="1"> <thead> <tr> <th>Surface Temperature</th> <th>Ambient Temperature</th> <th>Relative Humidity</th> </tr> </thead> <tbody> <tr> <td>Min: 10 °C</td> <td>Min: 10 °C</td> <td>Min: 10%</td> </tr> <tr> <td colspan="3">or 2 °C min. above dew point</td> </tr> <tr> <td>Max: 40 °C</td> <td>Max: 40 °C</td> <td>Max: 85%</td> </tr> </tbody> </table>	Surface Temperature	Ambient Temperature	Relative Humidity	Min: 10 °C	Min: 10 °C	Min: 10%	or 2 °C min. above dew point			Max: 40 °C	Max: 40 °C	Max: 85%
Surface Temperature	Ambient Temperature	Relative Humidity												
Min: 10 °C	Min: 10 °C	Min: 10%												
or 2 °C min. above dew point														
Max: 40 °C	Max: 40 °C	Max: 85%												
Storage & Packaging	Store away from direct sun, open flames and severe cold. Packaging: 500 ml.													
Surface Preparation	BARE WOOD: <ul style="list-style-type: none"> Remove excess resinous matter with a scraper and/or by sanding. Wipe down with PLASCON LACQUER THINNER (ILS 1) and a cloth. Sand in direction of grain with 150 grit paper. Remove dust with a damp cloth 													
Application	<ul style="list-style-type: none"> Ready for use. Brush over resinous or knotty areas. Apply a full even coat. 													
Caution	<ul style="list-style-type: none"> This product contains very volatile solvents. Keep container tightly closed when not in use. N.B. KNOT SEAL must be overcoated. 													
Safety Precautions	<ul style="list-style-type: none"> Always keep paint out of reach of children. Ensure good ventilation during application and drying. If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner. Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention. Harmful if swallowed. Seek medical attention and do not induce vomiting. Do not smoke while painting. Highly flammable. Store in a cool dry place away from heat and sparks. Refer to Safety Data Sheet for complete information. 													

WOODCARE KNOT SEAL

PRODUCT CODE: PK 2

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za